



36 Draffin Road Hilton, New York 14468
Phone: 585-392-3434
Toll Free: 1-800-828-6351
Sales: sales@monroefluid.com
Technical: technical@monroefluid.com

Monroe Cut 50 EPS

OVERVIEW

MONROE CUT 50 EPS is a cutting oil designed for use in screw machine applications or other machining applications that require the use of low-viscosity neat cutting oils. MONROE CUT 50 EPS is chlorine-free. MONROE CUT 50 EPS is formulated using additives to provide a clean and efficient operating environment, compared to traditional sulfurized cutting oils.

FEATURES & BENEFITS

- Low Odor
- Outstanding Lubricity for Superior Finishes
- Low Smoke
- Operator Friendly and Clean Running
- Compatible with all Materials
- Exceptional Cleanliness for Visibility
- Recommended for Screw Machines

APPLICATIONS

MONROE CUT 50 EPS can be used for centerless grinding, form grinding, creep feed grinding, plunge grinding, belt grinding and flute grinding. MONROE CUT 50 EPS can also be used for light machining operations.

RECOMMENDED CONCENTRATION

Use Monroe Cut 50 EPS as received. Do not mix Monroe Cut 50 EPS with water.

TYPICAL PROPERTIES

Appearance	Clear Amber liquid
Odor	Bland Petroleum
Chlorine	None
Specific Gravity	0.86
Viscosity, cSt/40°C	10-12 cSt

Material Safety Data Sheets are available for all products.
All reasonable care has been taken to ensure
that the above information is accurate as of the date of printing.