



36 Draffin Road Hilton, New York 14468
Phone: 585-392-3434
Toll Free: 1-800-828-6351
Sales: sales@monroefluid.com
Technical: technical@monroefluid.com

MONROE VANISHING OIL 145-50

OVERVIEW

MONROE VANISHING OIL 145-50 is an odorless, colorless, low-viscosity petroleum based product designed for light-gauge blanking, stamping or forming operations. MONROE VANISHING OIL 145-50 works well on ferrous and non-ferrous metals alike. MONROE VANISHING OIL 145-50 evaporates rapidly, leaving a slight residue which in most instances may be painted over without the need for additional cleaning operations. A test application with the particular paint/coating in question is recommended.

FEATURES & BENEFITS

- Mild Odor
- Fast Drying
- Non Gumming
- Leaves Transparent Film

APPLICATIONS

MONROE VANISHING OIL 145-50 may be applied by dipping, brushing, spraying, rolling or any other convenient method.

RECOMMENDED CONCENTRATION

Use Monroe Vanishing Oil 145-50 as received. Do not mix Monroe Vanishing Oil 145-50 with water.

TYPICAL PROPERTIES

Appearance-Concentrate	Water-clear liquid
Residual Film	Slight
Specific Gravity @ 60°F	0.8 ± 0.03
Lbs/Gallon	6.7 ± 0.1
Flash point, TCC	76°C/ 170°F

Material Safety Data Sheets are available for all products.
All reasonable care has been taken to ensure
that the above information is accurate as of the date of printing.