



36 Draffin Road Hilton, New York 14468  
Phone: 585-392-3434  
Toll Free: 1-800-828-6351  
Sales: sales@monroefluid.com  
Technical: technical@monroefluid.com

## MONROE VANISHING OIL 145-50 B

### OVERVIEW

MONROE VANISHING OIL 145-50 B is an odorless, colorless, low-viscosity petroleum based product designed for light-gauge blanking, stamping or forming operations. MONROE VANISHING OIL 145-50 B works well on ferrous and non-ferrous metals alike. MONROE VANISHING OIL 145-50 B evaporates rapidly, leaving a slight residue which in most instances may be painted over without the need for additional cleaning operations. A test application with the particular paint/coating in question is recommended.

### FEATURES & BENEFITS

- Mild Odor
- Fast Drying
- Non Gumming
- Leaves Transparent Film

### APPLICATIONS

MONROE VANISHING OIL 145-50 B may be applied by dipping, brushing, spraying, rolling or any other convenient method.

### MIXING

MONROE VANISHING OIL 145-50 B is intended to be used as received and is not dilutable with water.

### TYPICAL PROPERTIES

|                         |                    |
|-------------------------|--------------------|
| Appearance-Concentrate  | Water-clear liquid |
| Residual Film           | Slight             |
| Specific Gravity @ 60°F | 0.8 ± 0.03         |
| Lbs/Gallon              | 6.7 ± 0.1          |
| Flash point, TCC        | 76°C/ 170°F        |

Material Safety Data Sheets are available for all products.  
All reasonable care has been taken to ensure  
that the above information is accurate as of the date of printing.