



36 Draffin Road Hilton, New York 14468
Phone: 585-392-3434
Toll Free: 1-800-828-6351
Sales: sales@monroefluid.com
Technical: technical@monroefluid.com

MONROE VANISHING OIL 140 E5

OVERVIEW

MONROE VANISHING OIL 140 E5 is an odorless, colorless, low-viscosity petroleum solvent-based product designed for light-gauge blanking, stamping or forming operations and containing a lubricity additive to provide excellent results on thin-gauge stampings. MONROE VANISHING OIL 140 E5 works well on ferrous and non-ferrous metals alike. MONROE VANISHING OIL 140 E5 evaporates rapidly, leaving a slight residue which in most instances may be painted over without the need for additional cleaning operations. A test application with the particular paint/coating in question is recommended.

FEATURES & BENEFITS

- Mild Odor
- Fast Drying
- Non Gumming
- Leaves Transparent Film

APPLICATIONS

MONROE VANISHING OIL 140 E5 may be applied by dipping, brushing, spraying, rolling or any other convenient method.

MIXING

MONROE VANISHING OIL 140 E5 is intended to be used as received and is not dilutable with water.

TYPICAL PROPERTIES

Appearance-Concentrate	Milky white liquid
Residual Film	Slight
Specific Gravity @ 60°F	0.80 ± 0.03
Lbs/Gallon	6.7 ± 0.1
Flash point, TCC	62°C/ 143°F

Material Safety Data Sheets are available for all products.
All reasonable care has been taken to ensure
that the above information is accurate as of the date of printing.