



36 Draffin Road Hilton, New York 14468  
Phone: 585-392-3434  
Toll Free: 1-800-828-6351  
Sales: sales@monroefluid.com  
Technical: technical@monroefluid.com

## MONROE CUT 200 EPS

### OVERVIEW

MONROE CUT 200 EPS is a cutting oil designed for use in screw machine applications or other machining applications that require the use of higher-viscosity neat cutting oils. MONROE CUT 200 EPS is chlorine-free. MONROE CUT 200 EPS is formulated using additives to provide a clean and efficient operating environment, compared to traditional sulfurized cutting oils.

### FEATURES & BENEFITS

- Low Odor
- Outstanding Lubricity for Superior Finishes
- Low Smoke
- Operator Friendly and Clean Running
- Compatible with all Materials
- Exceptional Cleanliness for Visibility
- Recommended for Screw Machines

### APPLICATIONS

MONROE CUT 200 EPS can be used for centerless grinding, form grinding, creep feed grinding, plunge grinding, belt grinding and flute grinding. MONROE CUT 200 EPS can also be used for light machining operations. This product may also be used as an ISO 46 gear lubricant.

### RECOMMENDED CONCENTRATION

Use MONROE CUT 200 EPS as received. Do Not mix MONROE CUT 200 EPS with water.

### TYPICAL PROPERTIES

Appearance	Clear Amber liquid
Odor	Bland Petroleum
Chlorine	None
Specific Gravity	0.87
Viscosity @ 40°C	44-48 cSt

Material Safety Data Sheets are available for all products.  
All reasonable care has been taken to ensure  
that the above information is accurate as of the date of printing.