



36 Draffin Road Hilton, New York 14468
Phone: 585-392-3434
Toll Free: 1-800-828-6351
Sales: sales@monroefluid.com
Technical: technical@monroefluid.com

Monroe Grind 50 E

OVERVIEW

MONROE GRIND 50 E is a high-performance cutting and grinding oil.

APPLICATIONS

MONROE GRIND 50 E performs extremely well on ALL metals including Aluminum, Stainless Steel and exotic alloys. MONROE GRIND 50 E can be used for centerless grinding, form grinding, creep feed grinding, plunge grinding, belt grinding and flute grinding. MONROE GRIND 50 E can also be used for light machining operations.

RECOMMENDED CONCENTRATION

Use MONROE GRIND 50 E as received. Do Not mix MONROE GRIND 50 E with water.

TYPICAL PROPERTIES

| | |
|-------------------------|--------------------|
| Appearance | Clear Amber liquid |
| Residual Film | Soft, oily |
| Viscosity, cSt/40°C | 10.0 |
| Specific Gravity @ 60°F | 0.86 ± 0.01 |
| Lbs/Gallon | 7.14 ± 0.1 |
| Flash Point, COC °F | >300 |

Material Safety Data Sheets are available for all products.
All reasonable care has been taken to ensure
that the above information is accurate as of the date of printing.