



36 Draffin Road Hilton, New York 14468
Phone: 585-392-3434
Toll Free: 1-800-828-6351
Sales: sales@monroefluid.com
Technical: technical@monroefluid.com

MONROE 40-S

OVERVIEW

MONROE 40-S is a low viscosity general purpose machining oil. MONROE 40-S may be used on a variety of metals including steel, aluminum and brass as well as glass, stone and ceramics. MONROE 40-S is formulated without additives to provide a clean and efficient operating environment.

FEATURES & BENEFITS

- Low Odor
- Non-Staining
- Low Viscosity
- Operator Friendly and Clean Running
- Compatible with All Metals
- Exceptional Cleanliness for Visibility

APPLICATIONS

MONROE 40-S can be used for turning, broaching and other operations on most materials.

RECOMMENDED CONCENTRATION

Use MONROE 40-S as received. Do Not mix MONROE 40-S with water.

TYPICAL PROPERTIES

| | |
|-------------------------|--------------|
| Appearance | Clear liquid |
| Odor | Bland |
| Chlorine Content, % /wt | 0 % |
| Sulfur Content, % /wt | 0 % |
| Viscosity @ 40°C | 3 – 4.5 cSt |

Material Safety Data Sheets are available for all products.
All reasonable care has been taken to ensure
that the above information is accurate as of the date of printing.