



36 Draffin Road Hilton, New York 14468
Phone: 585-392-3434
Toll Free: 1-800-828-6351
Sales: sales@monroefluid.com
Technical: technical@monroefluid.com

MONROE DRAW 500 EP-EM

OVERVIEW

MONROE DRAW 500 EP-EM is a heavy duty rinseable drawing oil. It has been formulated for use on difficult drawing and blanking operations and has excellent adherence and anti-wipe properties. This product is well-suited for fine blanking operations on ferrous and stainless steels. It performs extremely well on both ferrous and non-ferrous metals without staining or rusting.

APPLICATIONS

MONROE DRAW 500 EP-EM may be applied by brushing, dipping, spraying, rolling or other convenient method.

RECOMMENDED CONCENTRATION

Use MONROE DRAW 500 EP-EM as received. Do Not mix MONROE DRAW 500 EP-EM with water.

TYPICAL PROPERTIES

| | |
|-------------------------|--------------------|
| Appearance | Clear Amber liquid |
| Residual Film | Soft, fluid |
| Viscosity @ 40°C | 150 cSt |
| Specific Gravity @ 60°F | 1.18 ± 0.01 |
| Lbs/Gallon | 9.84± 0.1 |
| Flash point, COC | >350°F |

Material Safety Data Sheets are available for all products.
All reasonable care has been taken to ensure
that the above information is accurate as of the date of printing.