



36 Draffin Road Hilton, New York 14468  
Phone: 585-392-3434  
Toll Free: 1-800-828-6351  
Sales: sales@monroefluid.com  
Technical: technical@monroefluid.com

## ASTRO-KOTE HF

### OVERVIEW

ASTRO-KOTE HF is a low-viscosity oil-based rust preventative coating designed to protect ferrous materials from rust. ASTRO-KOTE HF is a water-displacing product. This product is intended to be used as received. It is not to be mixed with water. ASTRO-KOTE HF may be used to protect castings, cast iron, steels and packaged parts from rust.

### FEATURES & BENEFITS

- Provides Up To One Year Indoor Storage Protection of Parts
- High Flash (125° C / 257 °F)
- Easily Removed With Warm Alkaline Cleaner or Solvent
- Leaves Slight Oily Film

### APPLICATIONS

ASTRO-KOTE HF may be applied by immersion, flooding, swabbing or other suitable method.

### MIXING

Astro-Kote HF is intended to be used as received and is not dilutable with water.

### TYPICAL PROPERTIES

Appearance-Concentrate	Clear Brown liquid
Residual Film	Soft Waxy/Oily
Viscosity, cSt/40°C	4.6
Specific Gravity @ 60°F	0.85 ± 0.03
Lbs/Gallon	7.1 ± 0.1
Flash point, PMCC	125 °C/ 257°F

Material Safety Data Sheets are available for all products.  
All reasonable care has been taken to ensure  
that the above information is accurate as of the date of printing.